


INSERT+ 2 V POST



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

- Post mounted outdoor luminaire for general lighting, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Inner satin toughened flat glass diffuser
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Static ON/OFF or dimmable DALI options available
 - Extruded aluminium post with base plate, polyester powder coat finish
 - Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
 - Rapid spring-type installation
 - No visible screws



INSERT+ 2 V POST 750

INSERT+ 2 V POST 750

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHT SOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634	GR-94	3118211	✓
9	I	-	80	3000	A/EW	-	1197	592	GR-94	3118209	✓
9	I	-	80	4000	A/EW	-	1318	634	AN-96	3118210	✓
9	I	-	80	3000	A/EW	-	1197	592	AN-96	3118208	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
9	I	-	80	4000	A/EW	-	1318	634	GR-94	3118215	✓
9	I	-	80	3000	A/EW	-	1197	592	GR-94	3118213	✓
9	I	-	80	4000	A/EW	-	1318	634	AN-96	3118214	✓
9	I	-	80	3000	A/EW	-	1197	592	AN-96	3118212	✓

