

MASK+ ROUND



Scan the QR-code for the latest information

- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall and ceiling mounted luminaire for indoor and outdoor, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium base for wall and ceiling applications, painted
- Glass diffusers, internally coated, for homogeneous light distribution
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Anti-ageing custom moulded silicone sealing gasket(s)
- Chromed steel spring locks for quick attachment of the body to the housing
- PIR versions have a motion sensor fitted into the ring, suitable for resistive and inductive load
- Sensor settings from 10 to 2000 lux
- Opening angle 120°
- Adjustable operation time (10 s to 7 min)
- Design by ROBERTO FIORATO




MASK+



MASK+ MINI



MASK+ ROUND



MASK+ ROUND
PIR

MASK+ ROUND

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	2650	1227	■	3105007	✓
22	I	-	80	3000	S/EW	-	2590	1188	■	3105005	✓
22	I	-	80	4000	S/EW	-	2650	1227	□	3105008	✓
22	I	-	80	3000	S/EW	-	2590	1188	□	3105006	✓



MASK+ ROUND PIR

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
22	I	-	80	4000	S/EW	-	2650	1227	■	3105011	✓
22	I	-	80	3000	S/EW	-	2590	1188	■	3105009	✓
22	I	-	80	4000	S/EW	-	2650	1227	□	3105012	✓
22	I	-	80	3000	S/EW	-	2590	1188	□	3105010	✓

