

MASK+ MINI




Scan the QR-code for the latest information


- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 1 kV
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel locking hardware
- Single (M) and dual (B) emission versions available
- Single emission models suitable for either upwards or downwards mounting (M options)
- PIR versions have a motion sensor fitted into the ring, suitable for resistive and inductive load
- Sensor settings from 10 to 2000 lux
- Opening angle 120°
- Adjustable operation time (10 s to 7 min)
- Design by ROBERTO FIORATO



PIR



MASK+ ROUND



MASK+ MINI PIR

MASK+ MINI M

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
8	I	-	80	4000	S/EW	-	733	340	■	3102527	✓
8	I	-	80	3000	S/EW	-	733	317	■	3101602	✓
8	I	-	80	4000	S/EW	-	733	340	□	3102528	✓
8	I	-	80	3000	S/EW	-	733	317	□	3101603	✓

MASK+ MINI M PIR

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
8	I	-	80	4000	S/EW	-	733	340	■	3104648	✓
8	I	-	80	3000	S/EW	-	733	317	■	3101606	✓
8	I	-	80	4000	S/EW	-	733	340	□	3104649	✓
8	I	-	80	3000	S/EW	-	733	317	□	3101607	✓

MASK+ MINI B

IP65 - IK05

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
16	I	-	80	4000	S/EW	-	1450	670	■	3102529	✓
16	I	-	80	3000	S/EW	-	1450	627	■	3101604	✓
16	I	-	80	4000	S/EW	-	1450	670	□	3102530	✓
16	I	-	80	3000	S/EW	-	1450	627	□	3101605	✓

