


QUASAR 60



Scan the QR-code for the latest information


- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

Wall-mounted LED luminaire, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Toughened flat glass diffuser, internally coated, for homogeneous light distribution
- Microprismatic, toughened, flat glass diffuser, silk-screened on the inside (TECH versions)
- Satin finish pure aluminium reflector (Al 99.98)
- Anti-ageing custom moulded silicone sealing gasket(s)
- Built-in driver
- Stainless steel locking hardware
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Openable and maintainable luminaire (future-proof)




Private villa - Sanlúcar de Barrameda - Cádiz - Spain



M / B



TECH / DOUBLE TECH



QUASAR 60

QUASAR 6o M

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	I	-	80	4000	A7/EW	-	2736	1655		3100821	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100818	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100822	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100819	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100823	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100820	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

19	I	-	80	4000	A7/EW	-	2736	1655		3100833	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100830	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100834	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100831	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100835	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100832	✓

QUASAR 6o M EM/3P

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
19	I	-	80	4000	A7/EW	-	2736	1655		3100845	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100842	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100846	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100843	✓
19	I	-	80	4000	A7/EW	-	2736	1655		3100847	✓
19	I	-	80	3000	A7/EW	-	2554	1631		3100844	✓

QUASAR 6o B

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
38	I	-	80	4000	A7/EW	-	5472	3250		3100857	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100854	✓
38	I	-	80	4000	A7/EW	-	5472	3250		3100858	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100855	✓
38	I	-	80	4000	A7/EW	-	5472	3250		3100859	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100856	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

38	I	-	80	4000	A7/EW	-	5472	3250		3100869	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100866	✓
38	I	-	80	4000	A7/EW	-	5472	3250		3100870	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100867	✓
38	I	-	80	4000	A7/EW	-	5472	3250		3100871	✓
38	I	-	80	3000	A7/EW	-	5107	3204		3100868	✓

QUASAR 6o TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
19	I	-	80	4000	A22/EW	-	2736	2078		3100815	✓
19	I	-	80	3000	A22/EW	-	2554	2050		3100812	✓
19	I	-	80	4000	A22/EW	-	2736	2078		3100816	✓
19	I	-	80	3000	A22/EW	-	2554	2050		3100813	✓
19	I	-	80	4000	A22/EW	-	2736	2078		3100817	✓
19	I	-	80	3000	A22/EW	-	2554	2050		3100814	✓

QUASAR 6o DOUBLE TECH

IP65 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
38	I	-	80	4000	A22/EW	-	5472	4082		3100851	✓
38	I	-	80	3000	A22/EW	-	5107	4026		3100848	✓
38	I	-	80	4000	A22/EW	-	5472	4082		3100852	✓
38	I	-	80	3000	A22/EW	-	5107	4026		3100849	✓
38	I	-	80	4000	A22/EW	-	5472	4082		3100853	✓
38	I	-	80	3000	A22/EW	-	5107	4026		3100850	✓

