





■ AN-96 / Anthracite gray / Textured
■ BK-81 / Black / Textured
■ INOX / Stainless steel / Matt

- Electropolished AISI 316 stainless steel or aluminium body and top-cap polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5) depending on versions
- UV stabilised transparent polycarbonate diffuser
- UV and heat stabilised high-transparency polycarbonate optics. The optical unit compartment features superior heat dissipation and IK10-rated impact resistance grating specific light distributions
- Aluminium heat sink
- Anti-ageing custom moulded silicone sealing gasket(s)
- Technopolymer electrical gearbox
- IP68-rated, loop-through, technopolymer box (WATER-STOP), connected with factory pre-wired H07RN-F cable to the luminaire, for cables Ø 7 - 13.5 mm
- Stainless steel locking hardware
- Die-cast aluminium floor mount base polyester powder coat finish prior chemical surface conversion
- AISI 304 stainless steel sheet metal sturdy bases for floor mounting are available as accessories. For purpose illumination: promoting safe navigation through campuses, car parks and public spaces
- Concrete installation fixing rods are available as accessories. Compatible with standard die-cast aluminium and optional stainless steel heavy use (HU) baseplates
- Design by SILVIA PAOLA PENNACCHIO



Technical drawing of a rectangular plate. The vertical dimension is labeled 900 and the horizontal dimension is labeled Ø155. The plate has a central white rectangular area and two gray rectangular areas at the top and bottom. Each gray area contains a small black dot. Dashed lines indicate the alignment of the central white area and the gray areas.



KHA TECH
9

KHA TECH 5 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENERG	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
15	II	-	80	4000	C/EW	-	2172	1587		3114016	✓
15	II	-	80	3000	C/EW	-	2100	1508		3114011	✓
15	II	-	80	4000	C/EW	-	2172	1587		3114014	✓
15	II	-	80	3000	C/EW	-	2100	1508		3114009	✓
15	II	-	80	4000	C/EW	-	2172	1587		3114018	✓
15	II	-	80	3000	C/EW	-	2100	1508		3114013	✓

KHA TECH 9 C/EW

IP66 - IK10 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENERG	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
15	II	-	80	4000	C/EW	-	2172	1587		3114006	✓
15	II	-	80	3000	C/EW	-	2100	1508		3114001	✓
15	II	-	80	4000	C/EW	-	2172	1587		3114004	✓
15	II	-	80	3000	C/EW	-	2100	1508		3113999	✓
15	II	-	80	4000	C/EW	-	2172	1587		3114008	✓
15	II	-	80	3000	C/EW	-	2100	1508		3114003	✓

Optional accessories


DESCRIPTION	COLOR	PART NUMBER	UKCA
KHA TECH			
AISI 316 stainless steel floor installation base		3114401	✓
AISI 316 stainless steel floor installation base		3114402	✓
Concrete mounting adaptor with stainless steel plate and galvanised steel rods		14049320	✓



3114401



3114402



14049320