


SMART [3]



Scan the QR-code for the latest information

■ Grey RAL 7035 / Grey RAL7035 /


Watertight fixture IP66/69/69 for industrial applications, ideal for production areas, warehouses, and logistics areas

- Designed to replace fluorescent devices and lowbays up to 6,500 lm
- IK08 body in RAL7035 colored self-exhausting polycarbonate
- Available in 3 sizes: 800 mm, 1200 mm and 1600 mm
- Available in 3000K, 4000K and 5700K with CRI ≥80
- Available with powers ranging from 18W to 58W and flux ranging from 1,700lm to 6,500lm
- Mid-power LED with wire bonding
- Available with integrated On/Off or DALI driver
- The through wiring version has pre-wired mechanical and electrical connections, allowing up to 25 fixtures installed in a continuous row
- Available in 2 different optical solutions: transparent or opal diffuser in UV-stabilized, self-extinguishing polycarbonate
- The device can be hung or wall-mounted through bracket accessory with a tilt of 30° or 45° on the vertical axis
- External emergency kit with 3h autonomy compatible with through wiring versions available (to be ordered separately)




Albinoleffe stadium - Zanica - Italy


Industrial






SMART [3]
800



SMART [3]
1200



SMART [3]
1600



SMART [3] 800 OPAL

IP66/69 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218P57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218P	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218P30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PL57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PL	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PL30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PD57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PD	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PD30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	OPAL	-	-	3200	■	GWS3218PLD57K	✓
27	II	✓	80	4000	OPAL	-	-	3200	■	GWS3218PLD	✓
27	II	✓	80	3000	OPAL	-	-	3000	■	GWS3218PLD30K	✓
15	II	✓	80	4000	OPAL	-	-	1600	■	GWS3118PLD	✓



SMART [3] 800 TRANSPARENT

IP66/69 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218T57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218T	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218T30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TL57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TL	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TL30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TD57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TD	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TD30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
27	II	✓	80	5700	TRNSP	-	-	3400	■	GWS3218TLD57K	✓
27	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3218TLD	✓
27	II	✓	80	3000	TRNSP	-	-	3200	■	GWS3218TLD30K	✓
15	II	✓	80	4000	TRNSP	-	-	1700	■	GWS3118TLD	✓



SMART [3] 1200 OPAL

IP66/69 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236P57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236P	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236P30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PL57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PL	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PL30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PD57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PD	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PD30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	OPAL	-	-	5000	■	GWS3236PLD57K	✓
40	II	✓	80	4000	OPAL	-	-	5000	■	GWS3236PLD	✓
40	II	✓	80	3000	OPAL	-	-	4800	■	GWS3236PLD30K	✓
20	II	✓	80	4000	OPAL	-	-	2500	■	GWS3136PLD	✓

SMART [3] 1200 TRANSPARENT

IP66/69 - IK08 - 850 °C



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236T57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236T	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236T30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TL57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TL	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TL30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TD57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TD	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TD30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
40	II	✓	80	5700	TRNSP	-	-	5200	■	GWS3236TLD57K	✓
40	II	✓	80	4000	TRNSP	-	-	5200	■	GWS3236TLD	✓
40	II	✓	80	3000	TRNSP	-	-	4900	■	GWS3236TLD30K	✓
20	II	✓	80	4000	TRNSP	-	-	2600	■	GWS3136TLD	✓

SMART [3] 1600 OPAL

IP66/69 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258P57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258P	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258P30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158P	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PL57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PL	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PL30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PD57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PD	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PD30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	OPAL	-	-	6400	■	GWS3258PLD57K	✓
50	II	✓	80	4000	OPAL	-	-	6400	■	GWS3258PLD	✓
50	II	✓	80	3000	OPAL	-	-	6100	■	GWS3258PLD30K	✓
26	II	✓	80	4000	OPAL	-	-	3250	■	GWS3158PLD	✓



SMART [3] 1600 TRANSPARENT

IP66/69 - IK08 - 850 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258T57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258T	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258T30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158T	✓
Power LED 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TL57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TL	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TL30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TL	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TD57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TD	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TD30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TD	✓
Power LED dimmable DALI 220-240 V 50/60 Hz - through-wiring											
50	II	✓	80	5700	TRNSP	-	-	6700	■	GWS3258TLD57K	✓
50	II	✓	80	4000	TRNSP	-	-	6700	■	GWS3258TLD	✓
50	II	✓	80	3000	TRNSP	-	-	6400	■	GWS3258TLD30K	✓
26	II	✓	80	4000	TRNSP	-	-	3400	■	GWS3158TLD	✓




Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
SMART [3]			
Wall-mounting bracket 30°/45°		GWS3191	✓
Rigid pipe adaptor		GWS3193	✓
Male connector 4 poles 10 A		GWS3194	✓
Continuous line connection kit		GWS3197	✓
Emergency kit 3h for through wiring version		GWS3198	✓
RINA clamp kit		GWS3296	✓



GWS3194



GWS3198



Orobia Climbing - Curno - Italy