


INSERT+ 1 V POST



Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured

- Post mounted outdoor luminaire for general lighting, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Inner satin toughened flat glass diffuser
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Extruded aluminium post with base plate, polyester powder coat finish
 - Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
 - Rapid spring-type installation
 - No visible screws



INSERT+ 1 V POST 600

INSERT+ 1 V POST 600

IP65 - IK06

LUMINAIRE VOLTAGE (V)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM-ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
4	I	-	80	4000	A/EW	-	418	197	■	3118477	✓
4	I	-	80	3000	A/EW	-	377	184	■	3118475	✓
4	I	-	80	4000	A/EW	-	418	197	■	3118476	✓
4	I	-	80	3000	A/EW	-	377	184	■	3118474	✓

