

ELIA BL




Scan the QR-code for the latest information


■ BK-RAL9005 / Black RAL9005 /

Die-cast aluminum luminaire for ground mounting, ideal for bollard lighting in residential areas and passageways:

- Designed in two different sizes (500mm and 700mm) with opal diffusing polycarbonate diffuser with double high and low emission) to create a comfortable atmosphere, color temperatures 3,000K, 4,000K and 5,700K and a color rendering index greater than 80
- It has been designed to withstand temperature variations from -20 ° C to + 45 ° C, water and dust penetration up to IP65 degree and shocks up to IK08 degree
- ELIA BL is easy to install thanks to the ground anchoring system with 4 blocking plugs



ELIA BL
L1 700



ELIA BL
M1 500

ELIA BL L1 700

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENERG	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	USCA
Power LED 100-240 V 50/60 Hz											
8	I	-	80	4000	OPAL	-	-	650	■	GWF2300PR840	✓
8	I	-	80	3000	OPAL	-	-	650	■	GWF2300PR830	✓



ELIA BL M1 500

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE [W]	CLASS	ENERG	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	USCA
Power LED 100-240 V 50/60 Hz											
8	I	-	80	4000	OPAL	-	-	650	■	GWF2300LR840	✓
8	I	-	80	3000	OPAL	-	-	650	■	GWF2300LR830	✓

