


BLIZ ROUND 30/40




Scan the QR-code for the latest information

- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured

- Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:
- Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Pressed glass diffuser, internally coated
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Through-wiring designed
 - 4000K and 3000K mid-power LED board
 - Built-in driver
 - Stainless steel locking hardware
 - Static ON/OFF or dimmable DALI options available
 - EM/3P version is designed for multipurpose 3 hours sustained emergency lighting



BLIZ ROUND
30



BLIZ ROUND
40

BLIZ ROUND 30

IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
30	I	-	80	4000	S/EW	-	4539	2343		304215	✓
30	I	-	80	3000	S/EW	-	4236	2178		304212	✓
30	I	-	80	4000	S/EW	-	4539	2343		304216	✓
30	I	-	80	3000	S/EW	-	4236	2178		304213	✓
30	I	-	80	4000	S/EW	-	4539	2343		304217	✓
30	I	-	80	3000	S/EW	-	4236	2178		304214	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304245	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304242	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304246	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304243	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304247	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304244	✓

Power LED - dimmable DALI 220-240 V 50/60 Hz

30	I	-	80	4000	S/EW	-	4539	2343		304227	✓
30	I	-	80	3000	S/EW	-	4236	2178		304224	✓
30	I	-	80	4000	S/EW	-	4539	2343		304228	✓
30	I	-	80	3000	S/EW	-	4236	2178		304225	✓
30	I	-	80	4000	S/EW	-	4539	2343		304229	✓
30	I	-	80	3000	S/EW	-	4236	2178		304226	✓

BLIZ ROUND 30 EM/3P

IP65 - IK08

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
21.5	I	-	80	4000	S/EW	-	3229	1673		304239	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304236	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304240	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304237	✓
21.5	I	-	80	4000	S/EW	-	3229	1673		304241	✓
21.5	I	-	80	3000	S/EW	-	3014	1555		304238	✓

BLIZ ROUND 40

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304257	✓
39	I	-	80	3000	S/EW	-	5798	2739		304254	✓
39	I	-	80	4000	S/EW	-	5998	2912		304258	✓
39	I	-	80	3000	S/EW	-	5798	2739		304255	✓
39	I	-	80	4000	S/EW	-	5998	2912		304259	✓
39	I	-	80	3000	S/EW	-	5798	2739		304256	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304269	✓
39	I	-	80	3000	S/EW	-	5798	2739		304266	✓
39	I	-	80	4000	S/EW	-	5998	2912		304270	✓
39	I	-	80	3000	S/EW	-	5798	2739		304267	✓
39	I	-	80	4000	S/EW	-	5998	2912		304271	✓
39	I	-	80	3000	S/EW	-	5798	2739		304268	✓

BLIZ ROUND 40 EM/3P

IP65 - IK06

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
39	I	-	80	4000	S/EW	-	5998	2912		304281	✓
39	I	-	80	3000	S/EW	-	5798	2739		304278	✓
39	I	-	80	4000	S/EW	-	5998	2912		304282	✓
39	I	-	80	3000	S/EW	-	5798	2739		304279	✓
39	I	-	80	4000	S/EW	-	5998	2912		304283	✓
39	I	-	80	3000	S/EW	-	5798	2739		304280	✓

