

SPILLO



■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Series of LED landscaping outdoor bollard and pole-top luminaires, comprising:


- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Anti-ageing custom moulded silicone sealing gasket(s)
- IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable
- Anti-tear cable gland M25x1.5 for cables Ø 9 - Ø 14 mm
- Stainless steel locking hardware
- Each LED can by-passed in case of failure thanks to a coupled electronic safety device (NUD)
- The Secure Light Distribution (SLD) system guarantees uniform light distribution even in the remote case of LED failures
- Supplied with 1m factory pre-wired HORN-5 cable
- Optimised asymmetric distribution for wide spacing and lighting-class levels matching (CP options)
- Built-in driver
- Glare control and upward light pollution laws compliant (0% ULOR rating)
- Design by ALESSANDRO PEDRETTI



Mitsui Outlet Park - Taichung - Taiwan




SPILLO MINI POST



SPILLO

Identifying and classifying our optics



SPILLO

IP65 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - with automatic power reduction 220-240 V 50/60 Hz											
44	II	-	70	4000	C/EW	-	6970	3733	■	304024	✓
Power LED dimmable 1-10 V 220-240 V 50/60 Hz											
44	II	-	70	4000	C/EW	-	6970	3733	■	303501	✓
44	II	-	70	4000	CP	-	6970	3998	■	303814	✓
24	II	-	70	4000	C/EW	-	3485	1767	■	303499	✓



Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UNITS
SPILLO			
Pole top adaptor Ø 60 mm	■	310403	✓
Pole top adaptor Ø 76 mm	■	310405	✓
Pole Spillo INT. 3.3 m	■	315023	✓
Pole Spillo F.T. 2.8 m with flange	■	315024	✓
Baseplate Spillo		310415	✓

