


SHIELD+ 1



■ AN-96 / Anthracite gray / Textured


Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-efficiency metallized technopolymer reflector with protective surface treatment
- Anti-ageing custom moulded silicone sealing gasket(s)
- Field settable integral tri-level lumen/wattage packages proprietary DIP switch driver
- Static ON/OFF or dimmable DALI options available
- EXTREME options are suitable for extreme operating temp. conditions, -40°C
- Through-wiring designed
- Twilight models (C versions) complete with dusk sensor available. Consult factory



Commercial Building Warmteservice - Gouda - Netherlands



SHIELD+ 1

SHIELD+ 1 MULTIPOWER

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
13							2080	1773			
19	I	-	80	4000	A/EW	-	2775	2364	■	3106354	✓
27							3605	3072			
13							2030	1621			
19	I	-	80	3000	A/EW	-	2700	2161	■	3106352	✓
27							3515	2808			



SHIELD+ 1 EXTREME-40°

IP66 - IK07

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
27	I	-	80	4000	A/EW	-	3605	3072	■	3106362	✓
27	I	-	80	3000	A/EW	-	3514	2808	■	3106360	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz											
27	I	-	80	4000	A/EW	-	3605	3072	■	3106358	✓
27	I	-	80	3000	A/EW	-	3514	2808	■	3106356	✓

