


SHIELD+ 2




■ AN-96 / Anthracite gray / Textured

Scan the QR-code for the latest information

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-efficiency metallized technopolymer reflector with protective surface treatment
- Anti-ageing custom moulded silicone sealing gasket(s)
- Static ON/OFF or dimmable DALI options available
- DALI versions have two drivers. Dual ignition is possible by assigning and managing addresses within the DALI protocol
- EXTREME options are suitable for extreme operating temp. conditions, -40°C
- EM/3P version is designed for multipurpose 3 hours sustained emergency lighting
- Li-Fe Po4 3,2 V 3.0 Ah batteries, 24 hours recharge time
- Through-wiring designed
- Twilight models (C versions) complete with dusk sensor available. Consult factory




SHIELD+ 2

SHIELD+ 2

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz											
79	I	-	80	4000	A/EW	-	10552	7985	■	3106328	✓
79	I	-	80	3000	A/EW	-	10284	7261	■	3106326	✓
52	I	-	80	4000	A/EW	-	7210	6070	■	3106332	✓
52	I	-	80	3000	A/EW	-	7028	5518	■	3106330	✓
Power LED - Emergency 3h - 220-240 V 50/60 Hz											
52	I	-	80	4000	A/EW	-	7210	6070	■	3106340	✓
52	I	-	80	3000	A/EW	-	7028	5518	■	3106338	✓



SHIELD+ 2 EXTREME-40°

IP66 - IK09

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz											
79	I	-	80	4000	A/EW	-	10552	7985	■	3106336	✓
79	I	-	80	3000	A/EW	-	10284	7261	■	3106334	✓

