



Scan the QR-code for
the latest information



- Extruded anodised aluminium housing
- Toughened, glass diffuser, silk-screened on the inside
- Coated die-cast aluminium end caps
- Anti-ageing custom moulded silicone sealing gasket(s)
- Complete with IP-rated through wiring connection box (WATER-STOP) for cables Ø 5 mm to Ø 13 mm
- High heat-dissipating aluminium gear tray for increased inner components lifespan
- Built-in driver
- Static ON/OFF or dimmable DALI options available
- Light colour and brightness dimming adjustable via Tunable White control system
- Tunable White (TW) options for dynamic lighting schemes CCT transition from 2700K to 6500K - (DALI DT8)
- DMX signal generator for RGBW versions available (ordered separately)
- Stainless steel springs for fixing the luminaire to the outer housing
- Recessed box to be ordered separately
- Through-wiring designed



Technical drawing of a rectangular plate. The top view shows a rectangle with a width of 100 and a length of 800. The side view shows a rectangle with a height of 120 and a length of 800. The drawing includes dashed lines to indicate the internal structure and the position of the plate.

Technical drawing of the dining table showing top and side views with dimensions:

- Top View:** Shows a rectangular table with a width of 100 and a length of 1300. The table has a central rectangular cutout.
- Side View:** Shows the table's profile with a height of 120. It features a thick top and a base with two horizontal support bars.



STRIP SQUARE+ INGROUND 550

IP67 - IK10



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
14	I	-	80	4000	A18/M	-	2130	1468		550	3109356	✓
14	I	-	80	4000	C/I	-	2130	1519		550	3109350	✓
14	I	-	80	4000	ELL	15°x45°	2130	1478		550	3109352	✓
14	I	-	80	4000	ELL	40°x60°	2130	1478		550	3109354	✓
14	I	-	80	3000	A18/M	-	2000	1374		550	3109355	✓
14	I	-	80	3000	C/I	-	2000	1425		550	3109349	✓
14	I	-	80	3000	ELL	15°x45°	2000	1384		550	3109351	✓
14	I	-	80	3000	ELL	40°x60°	2000	1384		550	3109353	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
14	I	-	80	4000	A18/M	-	2130	1468		550	3109388	✓
14	I	-	80	4000	C/I	-	2130	1519		550	3109382	✓
14	I	-	80	4000	ELL	15°x45°	2130	1478		550	3109384	✓
14	I	-	80	4000	ELL	40°x60°	2130	1478		550	3109386	✓
14	I	-	80	3000	A18/M	-	2000	1374		550	3109387	✓
14	I	-	80	3000	C/I	-	2000	1425		550	3109381	✓
14	I	-	80	3000	ELL	15°x45°	2000	1384		550	3109383	✓
14	I	-	80	3000	ELL	40°x60°	2000	1384		550	3109385	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
16	I	-	80	tw 2700-6500	ELL	15°x45°	2216	1142		550	3109413	✓

STRIP SQUARE+ INGROUND 550 RGBW

IP67 - IK10



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
15	III	-	80	rgbw 2700	ELL	15°x45°	1456	855		550	3109417	✓



STRIP SQUARE+ INGROUND 800

IP67 - IK10



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
20.5	I	-	80	4000	A18/M	-	3200	2136		802	3109364	✓
20.5	I	-	80	4000	C/I	-	3200	2216		802	3109358	✓
20.5	I	-	80	4000	ELL	15°x45°	3200	2152		802	3109360	✓
20.5	I	-	80	4000	ELL	40°x60°	3200	2152		802	3109362	✓
20.5	I	-	80	3000	A18/M	-	3000	2001		802	3109363	✓
20.5	I	-	80	3000	C/I	-	3000	2075		802	3109357	✓
20.5	I	-	80	3000	ELL	15°x45°	3000	2015		802	3109359	✓
20.5	I	-	80	3000	ELL	40°x60°	3000	2015		802	3109361	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
20.5	I	-	80	4000	A18/M	-	3200	2136		802	3109396	✓
20.5	I	-	80	4000	C/I	-	3200	2216		802	3109390	✓
20.5	I	-	80	4000	ELL	15°x45°	3200	2152		802	3109392	✓
20.5	I	-	80	4000	ELL	40°x60°	3200	2152		802	3109394	✓
20.5	I	-	80	3000	A18/M	-	3000	2001		802	3109395	✓
20.5	I	-	80	3000	C/I	-	3000	2075		802	3109389	✓
20.5	I	-	80	3000	ELL	15°x45°	3000	2015		802	3109391	✓
20.5	I	-	80	3000	ELL	40°x60°	3000	2015		802	3109393	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
22	I	-	80	tw 2700-6500	ELL	15°x45°	3324	1655		802	3109414	✓

STRIP SQUARE+ INGROUND 800 RGBW

IP67 - IK10



LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
21	III	-	80	rgbw 2700	ELL	15°x45°	2185	1174		802	3109418	✓



STRIP SQUARE+ INGROUND 1050

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
26	I	-	80	4000	A18/M	-	4260	2841		1054	3109372	✓
26	I	-	80	4000	C/I	-	4260	2946		1054	3109366	✓
26	I	-	80	4000	ELL	15°x45°	4260	2861		1054	3109368	✓
26	I	-	80	4000	ELL	40°x60°	4260	2861		1054	3109370	✓
26	I	-	80	3000	A18/M	-	4000	2660		1054	3109371	✓
26	I	-	80	3000	C/I	-	4000	2759		1054	3109365	✓
26	I	-	80	3000	ELL	15°x45°	4000	2680		1054	3109367	✓
26	I	-	80	3000	ELL	40°x60°	4000	2680		1054	3109369	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
26	I	-	80	4000	A18/M	-	4260	2841		1054	3109404	✓
26	I	-	80	4000	C/I	-	4260	2946		1054	3109398	✓
26	I	-	80	4000	ELL	15°x45°	4260	2861		1054	3109400	✓
26	I	-	80	4000	ELL	40°x60°	4260	2861		1054	3109402	✓
26	I	-	80	3000	A18/M	-	4000	2660		1054	3109403	✓
26	I	-	80	3000	C/I	-	4000	2759		1054	3109397	✓
26	I	-	80	3000	ELL	15°x45°	4000	2680		1054	3109399	✓
26	I	-	80	3000	ELL	40°x60°	4000	2680		1054	3109401	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
28	I	-	80	tw 2700-6500	ELL	15°x45°	4432	2252		1054	3109415	✓



STRIP SQUARE+ INGROUND 1050 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
27	III	-	80	rgbw 2700	ELL	15°x45°	2913	1624		1054	3109419	✓



STRIP SQUARE+ INGROUND 1300

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz												
33	I	-	80	4000	A18/M	-	5400	3549		1306	3109380	✓
33	I	-	80	4000	C/I	-	5400	3681		1306	3109374	✓
33	I	-	80	4000	ELL	15°x45°	5400	3575		1306	3109376	✓
33	I	-	80	4000	ELL	40°x60°	5400	3575		1306	3109378	✓
33	I	-	80	3000	A18/M	-	5000	3324		1306	3109379	✓
33	I	-	80	3000	C/I	-	5000	3447		1306	3109373	✓
33	I	-	80	3000	ELL	15°x45°	5000	3348		1306	3109375	✓
33	I	-	80	3000	ELL	40°x60°	5000	3348		1306	3109377	✓
Power LED - dimmable DALI 220-240 V 50/60 Hz												
33	I	-	80	4000	A18/M	-	5400	3549		1306	3109412	✓
33	I	-	80	4000	C/I	-	5400	3681		1306	3109406	✓
33	I	-	80	4000	ELL	15°x45°	5400	3575		1306	3109408	✓
33	I	-	80	4000	ELL	40°x60°	5400	3575		1306	3109410	✓
33	I	-	80	3000	A18/M	-	5000	3324		1306	3109411	✓
33	I	-	80	3000	C/I	-	5000	3447		1306	3109405	✓
33	I	-	80	3000	ELL	15°x45°	5000	3348		1306	3109407	✓
33	I	-	80	3000	ELL	40°x60°	5000	3348		1306	3109409	✓
TunableWhite Power LED - dimmable DALI DT8 - 220-240 V 50/60 Hz												
35	I	-	80	tw 2700-6500	ELL	15°x45°	5540	2867		1306	3109416	✓



STRIP SQUARE+ INGROUND 1300 RGBW

IP67 - IK10

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	LENGTH [mm]	PART NUMBER	UKCA
RGBW LED												
32	III	-	80	rgbw 2700	ELL	15°x45°	3209	1965		1306	3109420	✓



Control gear

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND			
Driver - CV 100 W - 48 V kit		310950	✓
Driver - CV 500 W - 48 V kit		310951	✓
STRIP SQUARE+ INGROUND RGBW			
Controller DMX touch white		3117844	✓
Controller DMX touch black		3117845	✓
USB key EcoEcco		3115612	✓



310950



310951



3117844



3117845



3115612

Mandatory accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND			
Recessed fixing kit L 590 mm		310422	✓
Recessed fixing kit L 842 mm		310423	✓
Recessed fixing kit L 1094 mm		310424	✓
Recessed fixing kit L 1346 mm		310425	✓



310422
310423
310424
310425



Complete unit	
1A+1B = please order 2 codes	
	components
A	gear body
B	recessed fixing kit

Optional accessories

DESCRIPTION	COLOR	PART NUMBER	UKCA
STRIP SQUARE+ INGROUND RGBW			
Box for RGBW continuous row		3109576	✓



3109576