


MANGO+ MIDI



☐ WH-RAL9010 / White RAL9010 / Textured


Scan the QR-code for the latest information

Recessed, modular, round LED downlight for indoor, comprising:

- Die-cast aluminium heat sink with Fast™ (Flexible air stream technology) cooling system grants an excellent dissipation and thermal management
- Injection-moulded ABS reflector with integral ceiling trim with light-tight connection to LED module
- Integrated diffuser grants an optimised uniformity
- Integral Dip-Switches to select one of two power levels, which can be field adjustable (MULTIPOWER models)
- Quick and toolless installation
- Rapid spring-type installation
- All components can be tool-less replaced lately
- Suitable for ceiling tile thickness from 1-25 mm



Tabor College Oscar Romero - Hoorn - Netherlands



MANGO+ MIDI

MANGO+ MIDI

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED - dimmable DALI 220-240 V 50/60 Hz										
15	II	-	-	80	4000	1980	1496	☐	3116576	✓
15	II	-	-	80	3000	1926	1455	☐	3116575	✓



MANGO+ MIDI MULTIPOWER

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
11.5 15	II	-	-	80	4000	1980 1520	1496 1150	☐	3109843	✓
11.5 15	II	-	-	80	3000	1925 1475	1455 1115	☐	3109842	✓
Power LED - emergency 1h - 220-240 V 50/60 Hz										
11.5 15	II	-	-	80	4000	1980 1520	1496 1150	☐	3109845	✓
11.5 15	II	-	-	80	3000	1925 1475	1455 1115	☐	3109844	✓



MANGO+ MIDI WIELAND MULTIPOWER

IP20 - IK07 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 220-240 V 50/60 Hz										
11.5	II	-	-	80	4000	1520	1150	☐	3109847	✓
15						1980	1496			
11.5	II	-	-	80	3000	1475	1115	☐	3109846	✓
15						1925	1455			

